

Sir:

Transmitted herewith for filing is the Patent Application of:

Inventor(s): **Dan Martin Scott and Darin Wayne Higgins**

For: **System and Method for Georeferencing Digital Raster Maps**

Enclosed are:

- ☒ Patent Specification and Declaration
- ☒ 4 sheets of drawing(s).
- ☒ An assignment of the invention to Provar Incorporated (includes Recordation Form Cover Sheet).
- ☒ A Declaration of Small Entity Status.
- ☐ Information Disclosure Statement, PTO 1449 and copies of references.

The filing fee has been calculated as shown below:

For	Number Filed	Number Extra	Rate	Fee
Basic Fee				\$345.00
Total Claims	16 - 20		x 18 =	\$
Indep. Claims	2 - 3		x 78 =	\$
MULTIPLE DEPENDENT CLAIM PRESENTED			x 260 =	\$
			TOTAL	\$ 345.00

Enclosed please find a check in the amount of \$690.00.

☒ The Commissioner is hereby authorized to charge payment of the following fees associated with this communication or credit any overpayment to Deposit Account 06-0580. A duplicate copy of this sheet is enclosed.

☒ Any additional filing fees required under 37 CFR §1.16.

☒ Any patent application processing fees under 37 CFR §1.17.

CERTIFICATE OF MAILING BY "EXPRESS MAIL" UNDER 37 CFR § 1.10

"Express Mail" mailing label number: EL497382408US

Date of Mailing: March 29, 2000

I hereby certify that the documents indicated above are being deposited with the United States Postal Service under 37 CFR 1.10 on the date indicated above and are addressed to Box Patent Applications, Assistant Commissioner for Patents, Washington, D.C. 20231 and mailed on the above Date of Mailing with the above "Express Mail" mailing label number.

Matthew S. Anderson
(name of person mailing paper)


SIGNATURE of person mailing paper or fee

Respectfully submitted,

By 

Matthew S. Anderson
Registration No. 39,093 for
FELSMAN, BRADLEY, VADEN,
GUNTER & DILLON, LLP
201 Main Street, Suite 1600
Fort Worth, Texas 76102
Telephone (817) 332-8143

The "Received" stamp of the Patent and Trademark Office imprinted hereon acknowledges the filing of:

- ☒ CIP Application 48 pgs
☒ Declaration (UNSIGNED)
☐ Assignment (w/PTO 1595)
☐ Formal Drawings _____ pgs
☐ Informal Drawings 6 pgs
☐ Continuation App'n
☐ Divisional App'n

- ☐ Amendment _____
☐ EOT _____ Mths
☐ Notice of Appeal
☐ Appeal _____
☐ Issue Fee _____
☒ Check(s) _____
☒ Post Card


Invention	SYSTEM AND METHOD FOR
Client	Source Prose, Corp.
Atty Docket#	108344-00010
Mailed:	Via Express Mailing EL840960246US w/cert. of Express mailing dated April 22, 2002
Filing Date:	April 22, 2002
Atty:	John D. Kaufmann
Serial No.:	Not Yet Assigned

Receipt Date & Serial No.



DOCKETED

by clag 5/13/02



NON-PROVISIONAL APPLICATION FOR U. S. PATENT UNDER 37
CFR 1.53(b)

TRANSMITTAL FORM

Attorney Docket No. 108344.000010
BOX PATENT APPLICATION
Assistant Commissioner for Patents
Washington, D. C. 20231

Sir:

Transmitted herewith for filing is the
patent application of:

"EXPRESS MAILING" Mailing Label No. EL840960246US

Date of Deposit: April 22, 2002

I hereby certify that this paper is being deposited with the U.S. Postal Service
Express Mail Post Office to Addressee Service under 37 CFR 1.10 on the date
shown above and is addressed to the BOX PATENT APPLICATION, Assistant
Commissioner for Patents, Washington, D.C. 20231.

Trish Paramore
Trish Paramore

Inventor(s): Scott, et al

For: SYSTEM AND METHOD FOR GEOREFERENCING MAPS

Enclosed are:

- 6 Sheets of informal drawings and 48 pages of Specification (including Abstract)
X A Declaration/Power of Attorney (UNSIGNED)
X Small Entity Status claimed under 37 CFR 1.27

This application is a continuation-in-part (CIP) of Serial No. 09/537,849, SYSTEM AND METHOD FOR
GEOREFERENCING DIGITAL RASTER MAPS, filed March 29, 2000.

FEE CALCULATION					FEE
	NUMBER		NUMBER EXTRA	RATE	BASIC FEE \$ 370.00
Total Claims	30	-20 =	10	X \$9 =	90.00
Independent Claims	2	-3 =	0	X \$42 =	0.00
Total Filing Fee					\$460.00

Please charge Deposit Account No. 50-1752 in the amount of the total fees set forth. The Assistant
Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit
Account No. 50-1752.

All correspondence related to this application may be addressed to Robert C. Klinger, Jackson Walker
LLP., 2435 North Central Expressway, Suite 600, Richardson, Texas 75080.

4/22/02
Dated

John D. Kaufmann
John D. Kaufmann
Reg. No. 24,017

ATTORNEY'S DOCKET NO.
108344-00010

APPLICATION FOR UNITED STATES PATENT
DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I declare that my residence, post office address and citizenship are as stated below next to my name; that I verily believe that I am the original, first and sole inventor if only one name is listed below, or an original, first and joint inventor if plural inventors are named below, of the subject matter which is claimed and for which a patent is sought on the invention entitled as set forth below, which is described in the attached specification; that I have reviewed and understand the contents of the specification, including the claims, as amended by any amendment specifically referred to in the oath or declaration; that no application for patent or inventor's certificate on this invention has been filed by me or my legal representatives or assigns in any country foreign to the United States of America; and that I acknowledge my duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, section 1.56(a);

I further declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

TITLE OF INVENTION:		SYSTEM AND METHOD FOR GEOREFERENCING MAPS
POWER OF ATTORNEY:		I HEREBY APPOINT THE FOLLOWING ATTORNEYS TO PROSECUTE THIS APPLICATION AND TRANSACT ALL BUSINESS IN THE PATENT AND TRADEMARK OFFICE CONNECTED THEREWITH
Robert C. Klinger, Reg. No. 34,365 T. Ling Chwang, Reg. No. 33,590 Bobby D. Slaton, Reg. No. 43,130		Camilo E. Adames, Reg. No. 47,221 Madelynn J. Farber, Reg. No. 45,410 Raffi J. Gostanian, Reg. No. 42,595
		Scott B. Stahl, Reg. No. 33,795 John Kaufmann, Reg. No. 24,017 Michael G. Cameron, Reg. No. P-50298
SEND CORRESPONDENCE TO: Robert C. Klinger Jackson Walker LLP 2435 North Central Expressway, Suite 600 Richardson, Texas 75080		DIRECT TELEPHONE CALLS TO: Robert C. Klinger 972-744-2902
NAME OF INVENTOR: (1) Dan Martin Scott	NAME OF INVENTOR: (2) Darin Wayne Higgins	NAME OF INVENTOR: (3)
RESIDENCE (City and State Only) Irving, Texas	RESIDENCE (City and State Only) Forth Worth, Texas	RESIDENCE (City and State Only)
POST OFFICE ADDRESS 4058 North Beltline Rd. #136 Irving, Texas 75038	POST OFFICE ADDRESS 125 Willow Ridge Rd. Forth Worth, Texas 76103	POST OFFICE ADDRESS
COUNTRY OF CITIZENSHIP: USA	COUNTRY OF CITIZENSHIP: USA	
SIGNATURE OF INVENTOR:	SIGNATURE OF INVENTOR:	SIGNATURE OF INVENTOR:
DATE:	DATE:	DATE:

SYSTEM AND METHOD FOR GEOREFERENCING MAPS

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation-in-part ("CIP") of US patent application, Serial
5 Number 09/537,849, filed 3/29/00 and shares specification and figures with commonly
assigned, copending US Patent Applications entitled "System and Method for Performing
Flood Zone Certifications" (Serial Number 09/537,161 filed March 29, 2000); a similarly
titled CIP of the '161 application, Serial Number , filed ; "System and
Method for Synchronizing Raster And Vector Map Images" (Serial Number 09/537,162
10 filed March 29, 2000); and a similarly titled CIP of the '162 application, Serial Number
, filed ; all of the foregoing being incorporated by reference hereinto.

FIELD OF THE INVENTION

The present invention generally relates to geographic map processing and, in
15 particular, to a system and method for georeferencing originally un-georeferenced
paper maps, that is, for assigning latitude and longitude references to paper maps
originally lacking them (or any other geographic referencing). More particularly, the
present invention relates to scanning un-georeferenced paper maps to produce un-

georeferenced digital raster maps, and then associating the digital raster maps with a geographic coordinate system. The present invention can be advantageously used to georeference flood maps published by FEMA.

BACKGROUND OF THE INVENTION

5

FEMA FLOOD MAPS

The Federal Emergency Management Agency (FEMA) publishes a large set of "flood maps." These paper maps are the official, Federally sanctioned source for determining flood risk. The flood maps delineate regions that are assigned a flood zone designation from among a limited set of possible designations.

10

For example, a region designated "Zone A" on a flood map is a high risk area, which FEMA believes has at least a 1 in 30 chance of flooding during any given year. A region designated "Zone V" combines the properties of a "Zone A" with the additional risk of wave action or flowing water. In the foregoing context, performing a "flood zone determination" (also known as a "flood hazard determination" or a "flood certification")

15

relative to a location entails a two-step process: (1) determining, based on FEMA flood maps and other materials, the FEMA-designated flood zone for the location in question, and, then, (2) completing required paperwork to report this determination (along with

certain other required information) to interested parties, such as home buyers, their lenders, and real estate brokers.

FEMA flood maps come in a variety of styles, but broadly speaking they can be divided into two types of maps, namely, index panels ("IP"), or index panel maps,

5 Figure 5, and regular panels ("RP"), or regular panel maps, Figures 1-4

Referring to Figure 1, a regular panel map 10 shows a relatively small geographic area at a fairly high level of detail. Each regular panel 10 depicts various "features" of the relevant area. these features include (without limitation) streets 12,13 railroad tracks 14, streambeds 16, lakes, intersections 18,20 of the foregoing, and detailed
10 delineations of the community borders and the boundaries of various extant flood zones (not shown in Figure 1, but see Figure 2) and their classifications.

Figure 2 depicts a regular panel map 10 in which flood zones 22 are depicted. As is typical, the flood zones 22 are denoted or "flagged" as variously shaded regions contained within irregular curvilinear boundaries (the "flood zone boundary"). Labels
15 30 on regular panels 10 designate the types of flood zones that have been shaded. With the exception of regular panels 10 described as "not printed" ("PNP") and panels 10 presenting flood zone-designated communities, described in greater detail below, all flood zone determinations are made by reference to appropriate regular panel maps 10.

Referring to Figures 1 and 2, each regular panel map 10 is bounded by a "neatline," that is, a rectangular frame or border 32 surrounding the geographic area of interest. The geographic area of interest may not completely "fill" the neatline 32, as indicated at 34 in Figure 1. For example, the actual geographic area contained within the neatline 32 of a regular panel 10 might consist of (a) a portion 33 of a community and the designated flood classification of the portion and (b) unincorporated or other portions 34 which surround, are surrounded by, or abut the community, and which have no flood classification depicted on the panel 10.

Referring to Figure 3, if FEMA has designated a regular panel map 10 as being applicable to determining the flood zone classification of only an incorporated community, designated at 42 in Figure 3, then the regular panel 10 cannot be used to determine the flood classification of any depicted unincorporated areas, designated at 34,36,38. According to FEMA protocol, the foregoing obtains whether or not flood zones for the unincorporated area are shown on the regular panel 10. Indeed, a FEMA panel map 10 often does not show flood zones for areas outside of the designated region for the map 10 (the designated region 42 is a portion of the community in this example). Sometimes the area outside of the designated area is just shown as a blank area on the panel, as at 34,36,38. Regardless of how much or how little detail is shown,

by convention, a flood determination can be made using a panel only in the region designated by FEMA.

The "inset" 44 of a panel 10 means any geographic region that is both shown on the panel and as to which FEMA mandates the flood zone designations set forth on the panel to be applied. A panel inset 10 may be self-connected (connected with all parts of itself) as in Figures 1-3, or, as shown in Figure 4, it may be split into two or more self-connected regions 46,48 by intervening non-designated areas 50 on the panel 10 and may include other non-designated areas, such as those shown at 52 and 54. The "insets" of a panel map 10 may comprise a collection of disjoint, self-connected regions 46,48 which collectively contain all of the designated area of the panel 10, and themselves constitute a subset of the geographic region contained within the neatlines 32.

Thus, from the foregoing, an actual map panel 10 consists, in general, of three parts: (1) the inset(s), (2) other (non-designated) geographic regions within the neatlines 32, but not included within the inset(s), and (3) areas of the panel which are outside of the neatlines 32, and generally show various types of textual information such as a map legend, the map panel number, and panel effective date, etc. It is true that, in the ideal case, the insets 46 and 48 should include only designated regions of the panel 10, but as a practical matter it is sometimes convenient for FEMA to include

some non-designated areas within the insets, so as to simplify the process of gathering inset border data.

Referring to Figure 5, an index panel map 60 shows a considerably broader area than a regular panel 10, but at a lesser degree of detail, and usually without the flood zones being indicated thereon. Typically, an index panel 60 shows a broad geographic view of the locations of the various regular panels 10 that make up an entire community, or large portion thereof. It should be noted that, while FEMA "defines" communities, these FEMA-defined communities often do not necessarily correspond to one's intuitive sense of what a community is.

10 The index panel 60, generally depicted in Figure 5, provides its broader, less detailed overview by displaying the neatline boundaries 32 of each of its regular panels 10 against a background of major geographic features (e.g. highways, lakes, etc.). Each of the regular panels' 10 neatline boundaries 32 is labeled with the corresponding number of its regular map panel, as represented by "XX," "YY" and "ZZ" in Figure 4..

15 Index maps 60, in effect, show how to "put together" the panel map 10 "jigsaw", that is, how to associate panel maps 10 with each other to form a grid thereof, grid lines 62 thereof being comprised of the aligned and/or overlapping neatlines 32 of adjacent panels 10.

Until the advent of the present invention, the primary purpose of the index maps 60 has been their use as an aid in manually determining which of the regular maps 10 should be consulted in order to make a flood zone determination. For example, if a property is known to be located in Community A, then a map analyst might first locate the property on the Community A index map 60. The analyst could immediately determine ---by examining the neatline borders 32,62 and the labels "XX," "YY," "ZZ" displayed on the index map 60--- which regular panel map 10 to consult. Since there are hundreds of panel maps 10 in the index map 60 of various communities, identification of a particular panel map 10 by examining an index map 60 can be effected more quickly than serially examining large numbers of panel maps 10. The present invention provides other, much more efficient ways of determining the correct regular panel map 10 applicable to a particular location.

Index maps 60 also contain neatline borders 32 for panel maps 10 that are not printed as such, and which are designated "panel not printed" or "PNP." As this name suggests, no actual panel map 10 is ever printed for a PNP. Instead, the relevant index map 60 displays the flood zone classification for the region contained within the PNP neatline borders 32. Accordingly, In the case of a PNP, the flood zone classification is determined from the index map 60, rather than from a regular panel 10.

In addition to the foregoing techniques, flood zone determinations can also be made on the basis of FEMA's denoting certain communities as "flood zone designated communities." In this event, FEMA mandates that a denoted community have the same flood zone classification throughout. As a consequence FEMA does not publish any flood panels ---either regular 10 or index 60--- for the community. Property located anywhere in that community assumes the flood zone classification of the community.

DIGITAL RASTER MAPS

A digital raster map image, Figure 2, may be thought of as a number of points selectively present on ---or missing from--- each X,Y coordinate of a Cartesian display. Points that are present are usually called "pixels." Besides having an address at an X,Y location, a pixel may have a "value," usually a numeric quantity designating a specified color or grey-scale value for the pixel. In this latter event, a "missing pixel" may be represented by a pixel having a value pursuant to which it is colored white. The X,Y location and value of each pixel is data that may be stored. A digital raster map may be created by optically, digitally scanning a conventional paper map and thereafter using a computer system to define and/or display it in terms of its pixel locations and color values. Commonly used formats for storing scanned images currently include TIFF, JPEG, and PNG. Any FEMA regular panel 10 or index panel 60 may be represented as a digital raster map.

DIGITAL VECTOR MAPS

A vector map, Figure 6, may be viewed as a "virtual" map that comprises, in effect, a collection of stored data. The stored data define the locations of plural nodes and plural straight line segments interconnecting the nodes. The stored data defining a
5 vector map represents geographic information in the form of collections of points ---the nodes--- and line segments interconnecting the nodes to form polygons, i.e., closed figures comprised of line-interconnected nodes. These points, lines, and polygons may have additional information associated with them. For example, the stored data may indicate that a particular point or node is the location of the capitol building, or that a
10 selected polygon describes the border of Lake Placid. The polygons are surrogates for, or representations of, the actual curvilinear configuration of various geographic features: streets, streams, lakes, cities, counties, etc. Typically, the features ---nodes alone or two or more interconnected nodes--- are presented in terms of latitude/longitude (or lat/lon) values. If this or another earth-referenced system is used
15 to locate the nodes of the map, the map is said to be georeferenced. A visually sensible map may be "drawn" from the stored data

In view of the fact that georeferencing of digital raster map images plays a key role in the present invention, the precise meaning of this term, for the purposes hereof and as used herein, is set forth below.

Georeferencing

A raster map image is said to be "georeferenced" if there exist mathematical functions, **f** and **g**, such that one function can be used to convert the X,Y coordinates of the pixels describing the map image to corresponding latitude/longitude coordinates and the other function can be used to convert the latitude/longitude coordinates of the pixels of the image to their corresponding X,Y coordinates. In other words, **f** and **g** effect the following:

1. If (x, y) represents a pixel location on a digital raster map image, then $f(x, y) = (\text{Lon}, \text{Lat})$ represents the longitude and latitude of the corresponding physical location; and
2. If (Lon, Lat) represents a physical location that lies within the region covered by the map, then $g(\text{Lon}, \text{Lat}) = (x, y)$ represents the point on the digital raster map image that corresponds to that longitude and latitude.

In the previous paragraph, (x,y) defines a point pursuant to the natural internal coordinate system of the raster map image. Most digital vector map images use longitude and latitude as their internal coordinate system. Accordingly, most digital vector maps can be considered to be trivially georeferenced *per se*. Most digital raster map images use the pixels of its image as a kind of natural coordinate matrix. Such a raster map image is not inherently trivially georeferenced and requires the operation of

a non-trivial georeferencing function to convert back and forth between coordinate systems.

Most FEMA maps do not contain any latitude/longitude information that would be useful in georeferencing their scanned raster image. Some recently FEMA-issued panels
5 do show latitude/longitude values at certain points thereon, but such panels are in a distinct minority when considered in the context of the 100,000+ panels that FEMA currently provides.

SUMMARY OF THE INVENTION

10 Pursuant to the present invention there is provided a system and method for georeferencing a digital raster map by associating specific points on the raster map with corresponding points on a georeferenced vector map or another georeferenced raster map. According to the preferred embodiment, a raster map and a corresponding vector map are simultaneously displayed to a user. The user then locates a common
15 geographic point or feature on each map, and marks each of them as a unique point-pair. When the user has marked at least two point-pairs, the system then computes a georeferencing function, based on the pixel-coordinates of the points marked on the raster map and the corresponding geographic coordinates of the points on the vector

map. Thereafter the geographic coordinates of any point on the map may be computed. As more point-pairs are identified, the georeferencing function is modified for increased accuracy.

A digital raster map is a computerized map image that resembles a conventional
5 paper map in that it presents an image of a mapped area, but is not associated with
any additional underlying data associated with the features of the map. A digital raster
map is typically created by scanning a conventional paper map, and is a grid-based map
composed of pixels (or points) of color, shades of grey or black and white. Each pixel
in the grid has can be referenced by X,Y pixel coordinates, and has only a value, which
10 indicates the color of that pixel. The pixels of a raster map are not, without more,
georeferenced, i.e., the pixels of a raster map cannot be identified by latitude/longitude
or other earth reference. Raster images are commonly referred to as "bit mapped."

A vector map comprises stored data defining nodes, lines and polygons, rather
than pixels, to describe an image. Unlike a raster map, in which the map image is
15 simply stored as a grid of pixels, when a vector map is displayed, it is "drawn" from a
set of underlying data. A vector map is created through the placements of nodes on a
plane and connecting those nodes with lines to form closed polygons. Vector lines can
be attributed with tables of data such as elevations, values, names or other information
relative to the line. Vector data can be displayed in three dimensions if the lines are

attributed with Z values, modified or changed relative to user need, or layered to allow for turning off and on the viewing of different information.

Because of their feature attribution properties, vector maps are particularly useful for displaying geographic data. Vector maps are used to display boundaries or
5 lines that denote the position and extent of features, such as county boundaries or lines denoting stream and river systems. It is also very easy to view or manipulate the data underlying a vector map, for example to view or change the elevation of a feature.

Also because vector maps are commonly drawn from a geographic data set describing the area shown, they are typically georeferenced. Georeferencing is the
10 process of relating source coordinates, such as X,Y Cartesian coordinates, to geographic coordinates, typically in standard latitude/longitude. An image or a vector file is georeferenced to be used within a mapping/geographic environment. In a vector map, the data from which the map is drawn typically includes a geographic coordinate set.

Modern GIS systems normally make use of digital vector map information.
15 However, a vast legacy of paper-based map information exists. It is very expensive and time consuming to convert all of the information on these paper maps over to a digital vector format. In many cases the scope and expense of such conversions render them completely impractical. However, even when a complete conversion to digital vector-based format is not possible, it is still possible to obtain some of the benefits of

computerized map systems in accordance with the present invention pursuant to which paper maps are converted to digital raster maps (by scanning them) and the raster image is thereafter georeferenced. After georeferencing, there is, according to the present invention, a definite mathematical relationship between the pixel coordinates in the raster map, and the geographic coordinates of the feature represented by that pixel. The present invention contemplates a system and method for georeferencing a raster map by associating points thereon with corresponding points on a previously georeferenced vector map. The invention is described as applicable to georeferencing FEMA flood maps, but may be used to georeference any non-georeferenced paper or other map.

First, using known scanning hardware and software, FEMA or other paper map images are scanned to create digital raster images thereof. The data representing the X,Y coordinates of the pixels comprising the raster images are stored in any convenient storage facility, such as computer memory or a CDROM. The stored raster images may be referred to herein as "flood map images."

Second, polygons that approximate the neatline borders of each panel map and polygons that approximate the inset boundaries of the flood map images within each panel map neatline are "captured." Both types of polygons (and other desired

polygons, e.g., those representing notable features on the paper map) are captured, by activating a device such as a mouse..

The capture of any of the foregoing polygons shown on the raster image, Figure 2, of a scanned paper map is achieved in the following manner. The user identifies the vertices (points) of the polygon by "clicking" a mouse icon, in order, on a suitable sequence of points on a displayed flood map image or raster image. The sequence of points may be "smooth" or may be angular, but, in any event, represents an approximation of the actual polygon. In the case of the neatlines, because such are rectangles, the polygon representation thereof and the actual neatline will be similar, if not the same. Because inset boundaries are often complexly curvilinear, a captured polygon representing an inset is likely to be less "smooth" than the actual polygon. Of course, smoothness may be increased by increasing the number of points or vertices captures in drawing the polygon. The order in which the user clicks on the vertices determines the order of traversal of the vertices of the polygon. As the user identifies a first and then subsequent vertices, a line segment is drawn from the previous vertex to the next identified vertex, until the polygon is completed upon subsequently clicking on the first vertex. The completed polygon is preferably displayed as overlying the displayed flood map image and may be edited, e.g., by adding additional vertices thereto to more accurately mimic the shape of the extant polygon.

Elementary tests for the correctness of the polygons thus defined and captured are preferably performed. These tests include at least a test to see that no edges of a polygon cross. Additional tests may include a test to see that no polygon edge is shorter than some edge length parameter, and a test to ensure that the edges defined
5 do form a closed polygon. These tests are applied on an ongoing basis, as the user determines additional vertices of the polygon. Errors may be highlighted in different colors or brought to the attention of the user through pop-up panels on the computer system. The user is allowed to edit the polygons to correct errors, or to improve their quality. Each polygon definition is stored, and once the map to which it relates is
10 georeferenced, the polygons ---that is, their vertices and lines--- will also be georeferenced,

Next, the flood map (digital raster) images are georeferenced. Initially, there is obtained or generated a digital vector map covering the same general geographic area covered by the flood map images and capable of displaying and depicting the same
15 geographic features, such as streets, rivers, railroads, etc. The digital vector map may be a commercially obtainable map covering a limited area or an entire geographic entity; vector maps covering the entire United States are available.

Then, the vector map image and the flood map image are simultaneously displayed. Such may result in the maps being displayed side-by-side, over-and-under,

or in superimposition. Using location information from the flood map image (e.g. county name, state, community name, large metropolitan area, etc.), the user manipulates the vector map (by zooming, panning, scrolling etc.) until it displays roughly the same region displayed in the flood map image.

- 5 The user then identifies a first point-pair, that is, a pair of points ---one point on the vector map, the other point on a selected (if more than one) inset of the flood image map--- that represent the same geographic location. Such point-pairs may be identified by "clicking" a mouse icon on an identifiable point on the flood map image--- say, a street intersection---and then "clicking" on the same point or street intersection
- 10 shown on the vector map. Accurate placement of the two points can be assured by zooming in on the images. Additional point-pairs (one point from the vector map, and one from the flood map image) are then identified.

As the second and subsequent point-pairs are each identified, an algorithm calculates and provides a georeferencing function correlating the flood map image and

15 the raster image. Specifically, upon identification of two point-pairs, a georeferencing function is generated and becomes available for the flood map image. This georeferencing function is refined as additional point-pairs are identified. As soon as a georeferencing function is available it is used to "synchronize" the vector map with the digital flood map image. The synchronized maps display the same geographic region,

and if one image is scrolled, panned, or zoomed by the user, the same manipulation occurs automatically in the other map image. The afore-noted "synchronization" greatly facilitates the placement of additional point-pairs, which improves the quality of the current georeferencing function. and is more specifically described in commonly
5 assigned US patent application Serial Number 537,161.

If multiple inset polygons have been defined on a single flood map image, and if those insets are not shown in their natural correct geographic relationship to one another, then it is necessary to calculate a different georeferencing function for each of the inset polygons. This situation occurs when FEMA shows a geographic region on one
10 map panel, which does not actually belong in the same geographic area as the rest of the map panel contents. FEMA sometimes does this in order to eliminate the necessity of printing another map with only a tiny region shown on it. In contemplation of this event, this step of the present invention is more generally stated as follows: When georeferencing an inset, the user must select only point-pairs contained within that
15 inset; a georeferencing function is calculated for each inset, and must be stored so that this correspondence is clear.

Using the foregoing approach, all FEMA flood map insets are georeferenced and stored. The georeferencing of the FEMA maps also georeferences the previously captured polygons representing the neatlines of the panel maps and the insets

therewithin. Accordingly, for every inset on a flood map, there exists a function which allows conversion of its X,Y pixel coordinates into lat/lon geographic coordinates. Among other things, such georeferencing implies that the boundaries of an inset itself -- -that is the stored polygon mimicking the inset boundaries--- can be expressed in terms
5 of lat/lon coordinates. More generally, any identifiable points or regions of a flood map image, including the borders of flood zone regions therein, can be expressed in lat/lon coordinates.

If an index map is initially georeferenced, as set forth above, then a preliminary georeferencing of a specific regular panel, the neatline of which is shown on the index
10 map, can be obtained by creating point-pairs out of the corresponding four corners of the neatline boundary which is, of course, shown on both the index map and the regular panel map. In other words, it is not really required for the georeferencing process that one of the maps be a vector map (although this is usually most convenient and practical). It is possible for both maps to be scanned raster map images, as long
15 as the same geographic region is depicted on each map and one map is already georeferenced.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features of the invention are set forth in the appended claims. The invention itself however, as well as its mode of use, further objects and advantages thereof, will best be understood by reference to the following detailed description read
5 in conjunction with the accompanying drawings, wherein:

Figures 1-4 are general representations of four FEMA panel maps, the insets of three of which do not fill the neatlines thereof and the inset of one of which does fill its neatlines;

Figure 5 is a general representation of a FEMA index map made up of a number
10 of the panel maps of Figures 1-4;

Figure 6 is a general representation of a vector map which corresponds to the raster map of Figure 2, in accordance with a preferred embodiment of the present invention;

Figure 7 is a flowchart of the process in accordance with the present invention:
15 and

Figure 8 is a depiction of a computer system for carrying out the method of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

The present invention is a system and method for georeferencing digital raster maps, Figures 1-5, by associating specific points on a raster map with corresponding points on a georeferenced vector map, Figure 6, or another georeferenced raster map.

5 Before georeferencing is initiated, the neatlines 32 of each raster map, such as Figure 2, are captured as polygons, and the polygons are then stored. Moreover, polygons mimicking the border of the inset(s), e.g., 33, 46, 48 in Figures 1, 3 and 4, are also captured and stored. The vertices and interconnecting lines of the polygons, and preliminary testing methods therefor are discussed above.

10 Next, a raster map, such as that shown in Figure 2, and a corresponding vector map, Figure 6, are simultaneously displayed to a user. The user then locates a common geographic point or feature on each map, Figures 2 and 6. Some corresponding points are numbered 200, 202, 204, 206 and 208 on both maps of Figures 2 and 6. Each set of common points 200-200, 202-202, 204-204, 206-206, and 208-208 is "marked" by
15 the user as a unique point-pair. Marking may be achieved in any convenient way, including "clicking" a mouse on each point of a point-pair so that the x,y coordinates of the point on the raster map of Figure 2 and the latitude/longitude coordinates of the point on the vector map of Figure 6 are captured and recorded.

When the user has marked at least two point-pairs, the system computes a georeferencing function, based on the x,y pixel coordinates of the points marked on the raster map of Figure 2 and the corresponding geographic coordinates of the points on the vector map of Figure 6. Thereafter the geographic coordinates of any point on the raster map of Figure 2 map may be easily computed. As more point-pairs are identified, the georeferencing function is modified for increased accuracy.

A digital map image is considered georeferenced if a pair of mathematical functions, **f** and **g** have been defined that can be used to convert back and forth between the coordinates of the raster map image of Figure 2 (as defined by the pixels of the image) and the corresponding longitude and latitude of the location of that point on the vector map of Figure 6. That is, georeferencing exists if the following are true:

1. If (x, y) represents a location on the digital raster map image (Figure 2), then $f(x, y) = (\text{Lon}, \text{Lat})$ represents the longitude and latitude of the corresponding physical location as depicted on the vector map (Figure 6).

2. If (Lon, Lat) represents a physical location that lies within the region covered by the vector map of Figure 6, then $g(\text{Lon}, \text{Lat}) = (x, y)$ represents the point on the digital raster map image of Figure 2 that corresponds to that longitude and latitude.

Here, x and y represent the natural internal coordinate system of the raster map image. Typically, as described above, the pixels of a digital raster map, as in Figure 2, constitute a natural internal coordinate system. A vector map, as in Figure 6, is based on a longitude and latitude coordinate system as its underlying coordinate system. As such, a vector map may be considered to be trivially georeferenced. Therefore, the functions f and g above are non-trivial georeferencing functions required to convert back and forth between the coordinate systems of the maps of Figure 2 and Figure 6.

Referring to Figure 7, first, the raster map, Figure 2, to be georeferenced is displayed on a computer monitor at the same time as a previously georeferenced map, Figure 6. **(step 400)**. Typically, the map of Figure 6 is a vector map, but could also be another raster map for which georeferencing functions are already known and can be accessed. The maps, Figures 2 and 6, are preferably displayed side by side, but may be displayed above and below, in superposition or in any other simultaneous or pseudo-simultaneous (e.g., back-and-forth toggling) display mode.

The maps of Figures 2 and 6 are preferably initially independently manipulable for rotation, position, pan, zoom and scale. The user is free to manipulate the display of both maps until the displayed region of the map in Figure 2 is generally shown in the display of the map of Figure 6.

Next, pairs of points, or point-pairs, 200-200, 202-202, etc, representing identical geographic locations on the maps of Figures 2 and 6 are identified, and the user uses a keyboard, mouse, or other pointing or capturing device to mark these point-pairs (**step 405**). For each point-pair, 200-200, etc., one point is marked on Figure 2 and the other point is marked at the corresponding location on Figure 6. The point marked on the raster map, Figure 2, has specific x,y coordinates. The same point marked on the vector map, Figure 6, has specific latitude,longitude coordinates. Examples of common georeferencing point-pairs include street intersections, 200-200, 202-202, 204-204 and 206-206, sites 208-208 where a road crosses a river, mountain peaks, specific building locations, the intersection of two rivers, and other readily identifiable map features.

If any points on the map of Figure 2 are identified on the map by longitude and latitude ---in the case of FEMA flood maps, this is a rare occurrence--- a georeferencing point-pair can be obtained by marking that point on Figure 2 and marking on Figure 6 at the location having the identical latitude and longitude. Alternatively, once such latitude,longitude-identified points on Figure 2 are marked, each will be associated with both lat,lon and x,y coordinates, and each can thereafter be used to determine the georeferencing functions without requiring a corresponding mark on Figure 6

After a point-pair is marked on Figures 2 and 6, the x,y coordinate on Figure 2 is assigned the corresponding latitude,longitude of its matching point on Figure 6 (**step**

412). When two georeferencing point-pairs are marked, the system computes an initial georeferencing function for Figure 2 based on a linear transformation that allows an arbitrary rotation and predefined scaling between the x,y domain and the latitude,longitude domain (**step 415**).

- 5 To improve accuracy and allow increased generality, more georeferencing point-pairs will frequently be desired. To facilitate the process of gathering these additional georeferencing point-pairs, the maps of Figures 2 and 6 are synchronized. Accordingly, as either map, Figure 2 or Figure 6, is zoomed, panned, scrolled, or otherwise caused to display a different region, the other map, Figure 6 or 2, automatically does the same.
- 10 This greatly increases the ease with which georeferencing point-pairs can be identified and marked on the maps, because, when the user of the system locates an identifiable feature on one map, the other map will automatically be showing substantially the same location.

- After synchronization is achieved, when the user marks a georeferencing point
- 15 on one of the maps, the system automatically marks the corresponding point on the other map in accordance with the last-calculated georeferencing function (**step 420**). The user can then make corrections to the location of a point marked by the system in this way (**step 425**). The user may enter as many point-pairs as are desired; each additional point-pair increases the accuracy of the georeferencing process.

When three or more georeferencing point-pairs are determined, the system computes a georeferencing function for Figure 2 based on a general linear transformation between the x,y domain and the latitude,longitude domain. When four or more georeferencing point-pairs are determined, the general linear georeferencing function is over-determined. This means that more than the required amount of information to compute the general linear georeferencing functions is available, but that this information may not be completely consistent. The system uses the extra information contained in the additional georeferencing points to provide validation checks to protect against the possibility that some of the data points may be inaccurate (step 430). Point-pairs that deviate excessively with respect to a calculated standard error are presumed to be inaccurate and are omitted from the extant calculation of the georeferencing function. As new point-pairs are added, the system rechecks previously omitted points to determine if those previously omitted points should now be considered when recomputing the georeferencing functions.

The additional point-pairs allow the system to compute the general linear georeferencing functions which best fit the combination of all the available georeferencing point-pairs, so that the active georeferencing functions are revised with each new point-pair (step 435). According to preferred embodiments, this is done by using a "least square" parameter fitting operation.

The user may then proceed to enter the next point-pair (**step 440**) . When the user is finished, the system stores the active georeferencing functions with the raster map of Figure 2 (**step 445**). At this time, the raster map is considered fully georeferenced and the related georeferencing functions are stored as is their association with the Figure 2. When the raster map is later accessed, the system retrieves the relevant georeferencing functions, and applies them to determine the latitude and longitude of any point on the raster map or to determine the x, y coordinates of any point on the vector map of Figure 6. Thus, at this time, the neatlines of each panel map, the boundary of each panel map inset and the "grid" of neatlines on each index map are, as polygons, fully georeferenced.

While various techniques exist for determining a georeferencing function from sets of point-pairs, the specific approach used by the system and method of the present invention is now discussed.

To carry out the georeferencing process of the present invention, sets of points P , are specified. Let $i \in P$ denote one of the points i of P . Associated value x_i, y_i and Lat_i, Lon_i refer, respectively, to the x and y coordinates of the point i on the raster map of Figure 2, and the latitude and longitude of the same point i on the earth's surface, i.e., on the vector map of Figure 6. There is also defined a set of points $A \subseteq P$, where A is the subset of "active" points, i.e. points which are in extant use in the

calculation of the georeferencing functions. A parametric family of functions \square is selected. It is stipulated that functions in this family \square map from (x, y) to (Lon, Lat) .

Any function $f \in \square$ has components $f_1(x, y) = Lon$, and $f_2(x, y) = Lat$. From within this family there is sought the specific function \hat{f} which (in a sense to be defined below)

5 introduces the smallest error in attempting to render the following system of equations true:

$$\hat{f}(x_i, y_i) = (Lon_i, Lat_i) \quad \text{for } i \in A \quad (1)$$

Once determined, \hat{f} will function as the georeferencing function which is used to compute corresponding latitude and longitude values (Lon, Lat) on the vector map of

10 Figure 6 for any point (x, y) on the raster map of Figure 2. There are a variety of ways to define the function that minimizes error in rendering Equation (1) true. The method of the present invention utilizes a least squares approach, known in mathematics as an L_2 approach. This approach seeks to ascertain the function \hat{f} which minimizes the sum of the squared differences between the actual and the predicted values of latitude and

15 longitude. In other words, from among all the functions $f \in \square$, \hat{f} is the one which minimizes:

$$SSE = \sum [(f_1(x_i, y_i) - Lon_i)^2 + (f_2(x_i, y_i) - Lat_i)^2] \quad (2)$$

Alternatively, the function \hat{f} may be chosen so that the sum of absolute errors, rather than squared errors, is minimized or so that the largest error is minimized. Other criteria are also possible.

In what follows there shall be described methods for computing georeferencing functions based on both a general linear parametric family of functions and a rotational linear family of functions. Those skilled in the art will readily perceive that this approach may be easily generalized to other parametric families of functions. One such other parametric family is a nonlinear parametric family of functions arising from the projection of the earth's surface onto a flat map.

The General Linear Case

In the general linear case, F is the set of all possible linear transformations which map from (x, y) to (Lon, Lat) . Thus,

$$\hat{f}(x, y) = \begin{bmatrix} \hat{a}_{11} & \hat{a}_{12} \\ \hat{a}_{21} & \hat{a}_{22} \end{bmatrix} \begin{bmatrix} x \\ y \end{bmatrix} + \begin{bmatrix} \hat{b}_1 \\ \hat{b}_2 \end{bmatrix} \quad (3)$$

for some choice of parameters \hat{a}_{11} , \hat{a}_{12} , \hat{a}_{21} , \hat{a}_{22} , \hat{b}_1 , and \hat{b}_2 . If the region covered by the map to be georeferenced is not too large, then this family of functions will contain a suitable function \hat{f} whose total error, as determined by the least squares

methodology, is quite small. In the case where the map to be georeferenced covers an area that is too large, the curvature of the earth must be taken into account and F is not a suitable family of functions. In the latter event, nonlinear functions must be used as mentioned above.

5 To find \hat{f} we seek the parameters which minimize

$$SSE = \sum_{i \in A} (a_{11}x_i + a_{12}y_i + b_1 - Lon_i)^2 + (a_{21}x_i + a_{22}y_i + b_2 - Lat_i)^2 \quad (4)$$

The parameter values which minimize this expression are found by solving the following two independent systems of linear equations:

10

$$\begin{bmatrix} n & \sum_{i \in A} x_i & \sum_{i \in A} y_i \\ \sum_{i \in A} x_i & \sum_{i \in A} x_i^2 & \sum_{i \in A} x_i y_i \\ \sum_{i \in A} y_i & \sum_{i \in A} x_i y_i & \sum_{i \in A} y_i^2 \end{bmatrix} \begin{bmatrix} b_1 \\ a_{11} \\ a_{12} \end{bmatrix} = \begin{bmatrix} \sum_{i \in A} Lon_i \\ \sum_{i \in A} x_i Lon_i \\ \sum_{i \in A} y_i Lon_i \end{bmatrix} \quad (5a)$$

$$\begin{bmatrix} n & \sum_{i \in A} x_i & \sum_{i \in A} y_i \\ \sum_{i \in A} x_i & \sum_{i \in A} x_i^2 & \sum_{i \in A} x_i y_i \\ \sum_{i \in A} y_i & \sum_{i \in A} x_i y_i & \sum_{i \in A} y_i^2 \end{bmatrix} \begin{bmatrix} b_2 \\ a_{21} \\ a_{22} \end{bmatrix} = \begin{bmatrix} \sum_{i \in A} Lat_i \\ \sum_{i \in A} x_i Lat_i \\ \sum_{i \in A} y_i Lat_i \end{bmatrix} \quad (5b)$$

These systems can be solved by well known methods, such as Gaussian Elimination or LU factorization. The solutions yield the desired values of \hat{a}_{11} , \hat{a}_{12} , \hat{a}_{21} , \hat{a}_{22} , \hat{b}_1 , and \hat{b}_2 . It should be noted that equations (5a) and (5b) do not have a unique solution unless three or more non-colinear points on the raster map, Figure 2, are contained in A. Generally speaking, then, it requires the selection of three point-pairs to initiate the calculation of a georeferencing function from the family of general linear transformations. When there are four or more point-pairs, it is possible to compute a standard deviation of errors using the formula:

$$s = \sqrt{\frac{\sum_{i \in A} \left[\left(\hat{a}_{11}x_i + \hat{a}_{12}y_i + \hat{b}_1 - Lon_i \right)^2 + \left(\hat{a}_{21}x_i + \hat{a}_{22}y_i + \hat{b}_2 - Lat_i \right)^2 \right]}{n-3}} \quad (6)$$

where s is an estimator for the amount of error to be expected between actual and predicted latitude and longitude values.

The inverse georeferencing function, \hat{f}^{-1} that maps from (Lon, Lat) of one point of a point-pair on the vector map of Figure 6 to (x,y) of the other point of the point-pair

on the raster map, Figure 2, may now be readily obtained by inverting the function \hat{f} . Having done this, it is possible to compute a similar standard deviation of error for \hat{f}^{-1} which is an estimate of error as measured in the x,y coordinates of the raster map of Figure 2.

5

The Rotational Linear Case:

In the rotational linear case, F is the set of all possible linear transformations which map from (x,y) to (Lon, Lat) and which also allow for a known scale change caused by the difference in distance per degree of latitude and per degree of longitude at any point not on the equator. Thus

$$\hat{f}(x,y) = \begin{bmatrix} \frac{\hat{\beta}_3}{\gamma} & -\hat{\beta}_4 \\ -\hat{\beta}_4 & -\hat{\beta}_3 \end{bmatrix} \begin{bmatrix} x \\ y \end{bmatrix} + \begin{bmatrix} \frac{\hat{\beta}_1}{\gamma} \\ \hat{\beta}_2 \end{bmatrix} \quad (7)$$

for some choice of parameters $\hat{\beta}_1$, $\hat{\beta}_2$, $\hat{\beta}_3$, and $\hat{\beta}_4$, where $\gamma = \cos(Lat)$ is computed from the estimated latitude of the map to be georeferenced. Clearly, this is a special case of the more general linear transform described above, where

15

$$a_{11} = \beta_3 / \gamma, a_{12} = -\beta_4, a_{21} = -\beta_4,$$

and

$$a_{22} = -\beta_3, b_1 = \beta_1 / \gamma, b_2 = \beta_2.$$

In theory, if the region covered by the raster map of Figure 2 to be georeferenced is not too large, then this family of functions will contain a suitable
5 function, \hat{f} whose total error is quite small. In the case where the map to be georeferenced covers a larger area than this, the curvature of the earth must be taken into account and F is not a suitable family of functions. In such a case, nonlinear functions must be used, as noted earlier. In practice, the general linear transform will yield results which are somewhat superior to the rotational linear transform due to the
10 former's innate ability to use arbitrary scaling factors. These arbitrary scaling factors might compensate, for example, for scaling flaws in the digital scanner used to scan in the non-georeferenced paper maps to produce maps like that of Figure 2. The primary advantage of the rotational linear transform is that it can be computed with only two reference point-pairs, while the general linear transform requires three reference point-
15 pairs.

To find \hat{f} there is sought, as before, the parameters which minimize SSE as defined in equation (4).

The parameter values which minimize this expression are found by solving the following system of linear equations:

$$\begin{bmatrix} n & 0 & \sum x_i & -\sum y_i \\ 0 & n & -\sum y_i & -\sum x_i \\ \sum_{i \in A} x_i & -\sum_{i \in A} y_i & \sum_{i \in A} (x_i^2 + y_i^2) & 0 \\ -\sum_{i \in A} y_i & -\sum_{i \in A} x_i & 0 & \sum_{i \in A} (x_i^2 + y_i^2) \end{bmatrix} \begin{bmatrix} \beta_1 \\ \beta_2 \\ \beta_3 \\ \beta_4 \end{bmatrix} = \begin{bmatrix} \gamma \sum_{i \in A} Lon_i \\ \sum_{i \in A} Lat_i \\ \gamma \sum_{i \in A} x_i Lon_i - \sum_{i \in A} y_i Lat_i \\ -\gamma \sum_{i \in A} y_i Lon_i - \sum_{i \in A} x_i Lat_i \end{bmatrix} \quad (8)$$

- 5 These systems can easily solved by well known methods, such as Gaussian Elimination, or LU factorization. The solutions yield the desire values of $\hat{\beta}_1$, $\hat{\beta}_2$, $\hat{\beta}_3$, and $\hat{\beta}_4$ which in turn yield the desired values for \hat{a}_{11} , \hat{a}_{12} , \hat{a}_{21} , \hat{a}_{22} , \hat{b}_1 , and \hat{b}_2 .

10 It should be noted that equation (8) does not have a unique solution unless two or more points are contained in **A**. Generally speaking, it requires two points to determine a georeferencing function from the family of rotational linear transformations. When there are three points or more, it is possible to compute a standard deviation of error, s using the formula:

$$s = \sqrt{\frac{\sum_{i \in A} \left[\left(\hat{a}_{11}x_i + \hat{a}_{12}y_i + \hat{b}_1 - Lon_i \right)^2 + \left(\hat{a}_{21}x_i + \hat{a}_{22}y_i + \hat{b}_2 - Lat_i \right)^2 \right]}{n-2}}$$

(9)

where s is an estimator for the amount of error to be expected between actual
5 and predicted latitude and longitude values.

The inverse georeferencing function \hat{f}^{-1} that maps from (Lon, Lat) to (x, y) is readily obtained by inverting the function \hat{f} . Having done this, it is possible to compute a similar standard deviation of error for \hat{f}^{-1} which is an estimate of error as measured in the bitmap coordinates.

10

Automatic Error Detection and Handling

When point-pairs are selected, the apparent values of x, y and Lon, Lat which are selected by mouse "clicking" may include error. To reduce the risk of incorrect georeferencing resulting from such errors, certain error handling procedures are built into the georeferencing process of the present invention. One technique utilized by the
15 present invention is to detect a "bad" point-pair and then remove it from the set **A** of "active" point-pairs, that is, those point-pairs presently involved in the calculation of a georeferencing function. Removing a bad point-pair from **A** does not delete the information associated with that point-pair. Rather, removing the bad point-pair causes

the extant calculation of the georeferencing parameters to be uninfluenced by that point-pair. The point-pair is not removed entirely, because it may be determined at a later stage of the georeferencing, that the point-pair was not really bad, and should be used in the georeferencing calculation. This will be clarified shortly.

5 The following steps outline the bad point detection process using the general linear transform approach to georeferencing.

(1) Place all point-pairs so far selected into the active set **A**. An "active" point-pair comprises a pair of points which are presently being used in the extant georeferencing calculation.

10 (2) If there are four or less active point-pairs, error correction cannot be performed and the georeferencing function cannot be refined.

(3) If there are five or more active point-pairs, temporarily exclude each of them in turn from the active set **A**, designating a temporarily excluded point-pair as **k**. With each point **k** excluded in turn, the calculate the inverse georeferencing function

15 $\hat{g}^{(k)}$ using the non-**k** point pairs. Calculate SSE_k for $\hat{g}^{(k)}$.

(4) Calculate the difference between the predicted value and the actual value $\delta_k = |\hat{g}^{(k)}(Lon_k, Lat_k) - (x_k, y_k)|$.

(5) Save the values, δ_k and δ_k / SSE_k .

(6) Return point k to the active set (and move on to the next value of k).

(7) From among the results found in steps (3)-(6), ascertain if there exists a point k , the absence of which from the calculation of the inverse function, leads to the largest values of $\delta_k / SSE_k > c_1$ and δ_k , where the value of δ_k also satisfies

5 $\delta_k / SSE_k > c_1$ and $\delta_k > c_2$, where c_1 , and c_2 are constants which are set according to the general level of accuracy to be expected on the particular type of map which is being georeferenced, the current number of active point-pairs, and the dots or pixels per inch of the raster image. If there is such a point, it is designated as erroneous and is removed from the active set A , and return to steps (2) and (3) above. If there is no
10 such point, error detection is completed.

The foregoing error detection may be, of course, carried out on a general purpose computer, preferably the same computer included in the system for manipulating the various maps and for calculating the georeferencing functions.

There are several things to note about the foregoing error detection procedure.

15 One is that allowing the value of c_1 and c_2 to change with the number of active point-pairs, makes it possible for the georeferencing system and method to utilize point-pairs which might originally have been determined as erroneous or inconsistent after a large enough sample of points has been gathered to make it clear that a lesser level of

accuracy is all that can be achieved on this map. Use of the error detection procedure of the present invention cannot reduce the number of active point-pairs to less than four. This scheme means that as each new point is added, all points determined so far are considered, even those which had previously been marked bad. Thus early
5 "misjudgements" on the part of the system can be corrected later, in light of new point information.

The same bad point detection process, can also be implemented when the rotational linear transform is used. In this case the method is capable of reducing the number of active point-pairs to a minimum of three, rather than four for the general
10 linear transform approach outlined above. This can be useful when dealing with small sets of active points.

When the system is georeferencing raster map images that cover a large enough area so that the (nonlinear) curvature of the earth is a source of significant error, the system can calculate nonlinear georeferencing functions whose form corresponds to the
15 map projection that was used to create the map of Figure 2.

A specific example of the operation and application of the preferred georeferencing method may be shown with reference to the "Flood Zone Determination" business. The Federal Emergency Management Agency (FEMA) publishes a library of tens of thousands of paper maps showing various types of flood

zones and their locations in the United States. A flood zone determination on a property is frequently done in the following way:

1. The address of the property is examined, and the location of the property is determined (perhaps through the use of a geocoding system, or by examining an available street map).

2. A map analyst attempts to determine which of the many thousands of FEMA flood maps will contain this property.

3. The map analyst goes to a map storage area and retrieves the desired map, often examining several maps before making a final selection.

4. Having retrieved the paper map, the map analyst next determines where, precisely, the property is located on the map.

5. Finally, the map analyst examines flood zone notations on the map at the property's location in order to determine its flood-zone status.

When performed using paper maps, the above process is difficult and quite time consuming . A database of scanned raster map images, alone, can be used to reduce the time and effort expended on step 3 above. However, georeferenced raster map images can also be used to eliminate virtually all work from steps 2 and 4 above. Since
5 those are generally the most time consuming steps under the current process, the value of georeferenced flood maps is considerable.

Using georeferenced flood map raster images, steps 2 and 4 above, are replaced by:

2'. A computer system combines the pre-designated outlines of the raster map
10 and the georeferencing information to obtain a polygon expressed in terms of latitude and longitude that outlines the region included in each flood map. Then the system determines which of the polygons contain the address in question, which is done using a "point-in-polygon" algorithm. At the conclusion of this process, the computer system has identified a map panel (or perhaps a small number of map panels) that
15 contains the address.

4'. Since the latitude and longitude of the property are known (by virtue of a geocoding phase), the computer system can use the georeferencing of the map panels to locate the property on each of the panels found above, thus largely eliminating any need for the map analyst to scan the flood map for the address location

Therefore, it is easily seen that by using georeferenced raster maps instead of paper maps, the process of determining flood zones is substantially automated and much more efficient.

It is important to note that while the present invention has been described in the context of a fully functional data processing system and/or network, those skilled in the art will appreciate that the mechanism of the present invention is capable of being distributed in the form of a computer usable medium of instructions in a variety of forms, and that the present invention applies equally regardless of the particular type of signal bearing medium used to actually carry out the distribution. Examples of computer usable mediums include: nonvolatile, hard-coded type mediums such as read only memories (ROMs) or erasable, electrically programmable read only memories (EEPROMs), recordable type mediums such as floppy disks, hard disk drives and CD-ROMs, an transmission type mediums such as digital and analog communication links.

While the invention has been particularly shown and described with reference to a preferred embodiment, it will be understood by those skilled in the art that various changes in form and detail may be made therein without departing from the spirit and scope of the invention.

WHAT IS CLAIMED IS:

1. A computer-implemented method of georeferencing an initially non-georeferenced raster map image, comprising the steps of:

(a) displaying a raster map and a georeferenced map that both depict the same geographic area;

(b) identifying at least two point pairs, each point pair comprising one point on the raster map and one point on the georeferenced map, each point of a point pair lying on the same geographic feature on both maps;

(c) with the use of the raster image coordinates of each point on the raster map and the geographic coordinates of the corresponding point on the georeferenced map, determining the functional relationships between the image coordinates and the geographic coordinates;

(d) thereafter, for each additional corresponding point-pair that is identified

(i) revising the functional relationships between the image coordinates and the geographic coordinates according to the additional point pairs, and

(ii) disregarding any points which are substantially inconsistent with the functional relationships.

2. A method as in Claim 1, wherein:

the image coordinates are Cartesian (x,y) coordinates, and the georeferenced map is a vector map having (latitude,longitude) coordinates.

3. A method as in Claim 1, wherein:

the maps are displayed substantially simultaneously in step (a).

4. A method as in Claim 1, wherein:

although the maps diversely depict the geographic area, certain geographic features and their intersections are displayed in common thereon.

5 5. A method as in Claim 4, wherein:

the identical geographic features include roads, streets, stream beds, railroad tracks, mountain peaks and buildings.

6. A method as in Claim 1, wherein:

10 in step (c), the functional relationships between the image coordinates and the geographic coordinates of the point pairs are calculated by selecting from a family of parametric equations the one equation that introduces the smallest error between the actual and predicted values of longitude and latitude assigned to (x,y) in the image.

7. A method as in Claim 6, wherein:

15 the one equation that introduces the smallest error is determined according to a least squares technique.

8. A method as in Claim 6, wherein:

the selection of an equation from a family of parametric equations is effected according to a general linear transform.

9. A method as in Claim 8, wherein:
at least three non-colinear point-pairs are identified.

10. A method as in Claim 6, wherein:
the selection of an equation from a family of parametric equations is
5 effected according to a rotational linear transform.

11. A method as in Claim 10, wherein:
at least two non-collinear point-pairs are identified.

12 A method as in Claim 1, further comprising:
10 storing the functional relationship with the raster map.

13. A method as in Claim 1, wherein:
the point pairs are identified in step (b) by a user marking them following
a visual determination that the geographic features on which they lie are the same

14. An item of commerce, comprising:
15 a computer-usable, portable memory unit containing the data of Claim 12.

15. An item of commerce, comprising:
a data transmission medium carrying the data of Claim 12.

16. An item of commerce, comprising:
a memory unit containing computer instructions for effecting the method
of Claim 1.

17. An item of commerce, comprising:
5 a data transmission medium connected to a general purpose computer for
instructing the computer to effect the method of Claim 1.

18. A computer system for georeferencing an initially non-georeferenced
raster map image, comprising:

10 (a) a monitor for displaying a raster map and a georeferenced map that
both depict the same geographic area;

(b) first facilities for identifying at least two point pairs, each point pair
comprising one point on the raster map and one point on the georeferenced map, each
point of a point pair lying on the same geographic feature on both maps;

15 (c) second facilities that use of the raster image coordinates of each point
on the raster map and the geographic coordinates of the corresponding point on the
georeferenced map, for determining the functional relationships between the image
coordinates and the geographic coordinates;

20 (d) third facilities for, after each additional corresponding point-pair is
identified, revising the functional relationships between the image coordinates and the
geographic coordinates according to the additional point pairs, while disregarding any
points which are substantially inconsistent with the functional relationships.

19. A system as in Claim 18, wherein:
the image coordinates are Cartesian (x,y) coordinates, and the
georeferenced map is a vector map having (latitude,longitude) coordinates.

5 20. A system as in Claim 18, wherein:
the maps are displayed substantially simultaneously by the monitor.

21 A system as in Claim 18, wherein:
although the maps diversely depict the geographic area, certain
geographic features and their intersections are displayed in common thereon.

10 22 A system as in Claim 21, wherein:
the identical geographic features include roads, streets, stream beds,
railroad tracks, mountain peaks and buildings.

23. A system as in Claim 18, wherein:
the second facilities calculate the functional relationships between the
image coordinates and the geographic coordinates of the point pairs by selecting from a
15 family of parametric equations the one equation that introduces the smallest error
between the actual and predicted values of longitude and latitude assigned to (x,y) in
the image.

24. A system as in Claim 23, wherein:
the one equation that introduces the smallest error is determined
20 according to a least squares technique.

25. A system as in Claim 23, wherein:
the selection of an equation from a family of parametric equations is
effected according to a general linear transform.

5 26. A system as in Claim 25, wherein:
at least three non-colinear point-pairs are identified.

27. A system as in Claim 23 wherein:
the selection of an equation from a family of parametric equations is
effected according to a rotational linear transform.


10 28. A system as in Claim 27, wherein:
at least two non-colinear point-pairs are identified.

29 A system as in Claim 18, further comprising:
fourth facilities for storing the functional relationships together with the
raster map.

15 30. A system as in Claim 18, wherein:
the first facilities include a device by which a user can mark the points of a
point pair following a visually determining from the monitor that the geographic
features on which the points lie are the same.

ABSTRACT OF THE DISCLOSURE

After FEMA paper flood maps are scanned into a computer system, they are each displayed side-by-side with the relevant portion of a stored vector map covering the geographic area covered by all of the FEMA maps. During display, corresponding points, or "point-pairs," on each map are marked by a keyboard or mouse device. The corresponding points may be such artifacts as roads, stream beds, railroad tracks, intersections of the foregoing, buildings, mountain peaks, etc., which are identifiable on each displayed map. When two point-pairs are marked, a stored algorithm calculates georeferencing functions which permit translation of the x,y coordinates of the raster map to the latitude,longitude coordinates of the vector map and *vice versa*. As more point-pairs are marked, the georeferencing functions are refined. Another algorithm removes apparent "bad" points from the georeferencing calculations, which points may be later used if it appears that they are not bad.






FIG. 2

3/5




FIG. 4







FIG. 5

FIG. 6



5/5

FIG. 7






POST OFFICE TO ADDRESSEE



EL 840960246 US



SEE REVERSE SIDE FOR
SERVICE GUARANTEE AND LIMITS
ON INSURANCE COVERAGE

Customer Copy
Label 11-F August 2000

ORIGIN (POSTAL USE ONLY)

PO ZIP Code 75080	Day of Delivery <input checked="" type="checkbox"/> Next <input type="checkbox"/> Second	Flat Rate Envelope <input type="checkbox"/>
Date In 4/22/02	<input checked="" type="checkbox"/> 12 Noon <input type="checkbox"/> 3 PM	Postage \$ 16.25
Time In 11:15	Military <input type="checkbox"/> 2nd Day <input type="checkbox"/> 3rd Day	Return Receipt Fee
Weight lbs 10.9 ozs	Int'l Alpha Country Code	COD Fee Insurance Fee
No Delivery <input type="checkbox"/> Weekend <input type="checkbox"/> Holiday	Acceptance Clerk Initials [Signature]	Total Postage & Fees \$ 16.25

<input type="checkbox"/> WAIVER OF SIGNATURE (Domestic Only): Additional merchandise insurance is void if waiver of signature is requested. I wish delivery to be made without obtaining signature of addressee or addressee's agent (if delivery employee judges that article can be left in secure location) and I authorize that delivery employee's signature constitutes valid proof of delivery.	
NO DELIVERY: <input type="checkbox"/> Weekend <input type="checkbox"/> Holiday	Customer Signature

CUSTOMER USE ONLY

METHOD OF PAYMENT:

Express Mail Corporate Acct. No.

Federal Agency Acct. No. or
Postal Service Acct. No.

FROM: (PLEASE PRINT)

PHONE

972 744-2905

JACKSON WALKER LLP
2435 N CENTRAL EXPY STE 600
RICHARDSON TX 75080-2719
USA

TO: (PLEASE PRINT)

PHONE

COMMISSIONER FOR PATENTS
AND TRADEMARKS
WASHINGTON DC 20231-0001

Exp: CIP Application

Source Phone 108344-00010

FOR PICKUP OR TRACKING CALL 1-800-222-1811

www.usps.com





EL 840960246 US

**POST OFFICE
TO ADDRESSEE**

ORIGIN (POSTAL USE ONLY)			DELIVERY (POSTAL USE ONLY)		
PO ZIP Code	Day of Delivery <input type="checkbox"/> Next <input type="checkbox"/> Second	Flat Rate Envelope <input type="checkbox"/>	Delivery Attempt	Time <input type="checkbox"/> AM <input type="checkbox"/> PM	Employee Signature
Date In Mo. Day Year	<input type="checkbox"/> 12 Noon <input type="checkbox"/> 3 PM	Postage \$	Delivery Attempt	Time <input type="checkbox"/> AM <input type="checkbox"/> PM	Employee Signature
Time In <input type="checkbox"/> AM <input type="checkbox"/> PM	Military <input type="checkbox"/> 2nd Day <input type="checkbox"/> 3rd Day	Return Receipt Fee	Delivery Date	Time <input type="checkbox"/> AM <input type="checkbox"/> PM	Employee Signature
Weight lbs. ozs.	Int'l Alpha Country Code	COD Fee Insurance Fee	<input type="checkbox"/> WAIVER OF SIGNATURE (Domestic Only): Additional merchandise insurance is void if waiver of signature is requested. I wish delivery to be made without obtaining signature of addressee or addressee's agent (if delivery employee judges that article can be left in secure location) and I authorize that delivery employee's signature constitutes valid proof of delivery.		
No Delivery <input type="checkbox"/> Weekend <input type="checkbox"/> Holiday	Acceptance Clerk Initials	Total Postage & Fees \$	NO DELIVERY <input type="checkbox"/> Weekend <input type="checkbox"/> Holiday Customer Signature		

CUSTOMER USE ONLY	
METHOD OF PAYMENT: Express Mail Corporate Acct. No.	
FROM: (PLEASE PRINT) JACKSON WALKER LLP 2435 N CENTRAL EXPY STE 600 RICHARDSON TX 75080-2719 USA Source Prose 108344-00010	TO: (PLEASE PRINT) COMMISSIONER FOR PATENTS AND TRADEMARKS WASHINGTON DC 20231-0001 Box: CIP Application

PRESS HARD. You are making 3 copies. **FOR PICKUP OR TRACKING CALL 1-800-222-1811** www.usps.com

Mailing Label

FC
T2

82

The "Received" stamp of

EL 840960246US

... printed hereon acknowledges the filing of:

<input checked="" type="checkbox"/> CIP Application 48 pgs	<input type="checkbox"/> Amendment
<input checked="" type="checkbox"/> Declaration (UNSIGNED)	<input type="checkbox"/> EOT Mths
<input type="checkbox"/> Assignment (w/PTO 1595)	<input type="checkbox"/> Notice of Appeal
<input type="checkbox"/> Formal Drawings pgs	<input type="checkbox"/> Appeal
<input type="checkbox"/> Informal Drawings 6 pgs	<input type="checkbox"/> Issue Fee
<input type="checkbox"/> Continuation App'n	<input checked="" type="checkbox"/> Check(s)
<input type="checkbox"/> Divisional App'n	<input checked="" type="checkbox"/> Post Card

Invention	SYSTEM AND METHOD FOR	Receipt Date & Serial No.
Client	Source Prose, Corp.	
Atty Docket#	108344-00010	
Mailed:	Via Express Mailing EL840960246US w/cert. of Express mailing dated April 22, 2002	
Filing Date:	April 22, 2002	
Atty:	John D. Kaufmann	
Serial No.:	Not Yet Assigned	